

ВЫВОДНОЙ СВЕТОДИОД КРУГЛЫЙ

ARL-5053RGBC/4C

FEATURES

- Uniform light output.
- Low power consumption.
- I.C. compatible.
- Long life — solid state reliability.
- Common anode.

DESCRIPTIONS

- The Red source color devices are made with AlGaInP on GaAs substrate Light Emitting Diode.
- The Green source color devices are made with InGaN on SiC Light Emitting Diode.
- The Blue source color devices are made with InGaA1N on SiC Light Emitting Diode.

APPLICATIONS

- Status indicators.
- Commercial use.
- Advertising signs.
- Back lighting.

DEVICE SELECTION GUIDE

LED Part No.	CHIP		Lens Color
	Material	Emitted Color	
ARL-5053RGBC/4C	AlGaInP	Red	Water clear
	InGaN	Green	
	InGaN	Blue	



5 mm



CLEAR



RGB



USAGE NOTES:

The ultra bright LED is an electrostatic insensitive device, so static electricity and surge will damage the LED.

It is required to wear a wrist-band when handling the LED.


All device, equipment, machinery, desk and ground must be properly grounded.

When using LED, it must use a protective resistor in series with DC current about 20 mA.



ATTENTION!
ELECTROSTATIC SENSITIVE DEVICES.
OBSERVE PRECAUTIONS FOR HANDLING.

PACKAGE DIMENSIONS



Unit: mm.

Notes:

Other dimensions are in millimeters, tolerance is 0.25 mm except being specified.

Protruded resin under flange is 1.5 mm Max LED.

Bare copper alloy is exposed at tie-bar portion after cutting.

ABSOLUTE MAXIMUM RATING ($T_A = +25^\circ\text{C}$)

Parameter	Symbol	Absolute Maximum Rating	Unit
Forward Pulse Current	I_{FPM}	R:60 G:100 B:100	mA
Forward Current	I_{FM}	20	mA
Reverse Voltage	V_R	5	V
Power Dissipation	P_D	R:60 G:130 B:130	mW
Operating Temperature	T_{opr}	-40... +80	°C
Storage Temperature	T_{stg}	-40... +100	°C
Soldering Heat (5s)	T_{sol}	Reflow Soldering: 260 °C for 10 sec. Hand Soldering: 350 °C for 3 sec.	°C

ELECTRO-OPTICAL CHARACTERISTICS ($T_A = +25^\circ\text{C}$)

Parameter	Symbol	Device	Min.	Typ.	Max.	Unit	Test Condition
Luminous Intensity	I_v	Red	400	—	500	mcd	$I_f=20\text{mA}$
		Green	800	—	1200		
		Blue	300	—	500		
Viewing Angle	$2\theta_{1/2}$	Red	80	—	100	Deg	(Note 1)
		Green					
		Blue					
Peak Emission Wavelength	λ_P	Red	625	630	640	nm	$I_f=20\text{mA}$
		Green	520	525	530		
		Blue	460	465	470		
Spectral Line Half-Width	$\Delta\lambda$	Red	15	20	25	nm	$I_f=20\text{mA}$
		Green	15	20	25		
		Blue	25	30	35		
Forward Voltage	V_F	Red	2.9	—	2.4	V	$I_f=20\text{mA}$
		Green			3.3		
		Blue			3.3		
Reverse Current	I_R	Red	—	—	10	μA	$V_R=5\text{V}$
		Green					
		Blue					


Note:

1. Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.


2. $\theta_{1/2}$ is the off-axis angle at which the luminous intensity is half the axial luminous intensity.

TYPICAL ELECTRO-OPTICAL CHARACTERISTICS CURVES


Relative Intensity VS Wavelength




Forward Current VS Forward Voltage




Relative Intensity VS Ambient Temp




Forward Current VS Relative Intensity



Forward Current VS Ambient Temp



Radiation Characteristics



NOTES

1. Above specification may be changed without notice. Hyled will reserve authority on material change for above specification.
2. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. Hyled assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
3. These specification sheets include materials protected under copyright of Hyled corporation. Please don't reproduce or cause anyone to reproduce them without Hyled's consent.